

team centaur**frame kit**

frame	Slyway	AL 7020	1700 gr
front boom	Slyway	AL 7020 L 360 mm	380 gr
front fork	Slyway team 650 carbon	T700 Carbon fiber	350 gr
seat	Slyway Morpheus	AL 6082	875 gr
seat post	Slyway V-post	AL 7020	200 gr
stem	Slyway Fixy	AL 7003	280 gr
handlebar	ITM Mustache narrow	L 350 mm	140 gr
headset	Tange	1" 1/8	
bolts	inox		
colour (gloss)	black&white		

drive train

cranck	Campagnolo Chorus Ultra Torque Carbon	53-39	679 gr
bottom bracket	campagnolo Record Ultra Torque		49 gr
cassette	Campagnolo Centaur	10 speed 12-25	233 gr
rear derailleur	Campagnolo Centaur		232 gr
front derailleur	Campagnolo Centaur		86 gr
shifters	Campagnolo Time Trial Bar End		163 gr
chain	Campagnolo Chours Ultra Narrow	10 speed	2,36 gr / link
pedals	not included		

brakes

brakes	Campagnolo Centaur Skeleton		334 gr
brake levers	Tektro RL 720		90 gr pair

wheel set

front wheel	Gipiemme 716 Twin	650 c	910 gr
rear wheel	Gipiemme 716 Twin	650 c	1080 gr
tires	Schwalbe Stelvio	650x23c 23-571	430 gr pair
tubes	Schwalbe extralight SV11		120 gr pair

price

SRP bike	€ 2.962
SRP frame kit	€ 1.488

options

seat pad	Ventisit open structure	400 gr	€ 75,0
seat pad	Slyway light set	100 gr	€ 11,7
seat pad	Slyway comfort set	400 gr	€ 16,7
seat cover	Threeface	120 gr	€ 24,2

frame upgrade

seat post	Slyway X-post carbon	130 gr	€ 167,0
-----------	----------------------	--------	---------

bike upgrade

cranck set	Extralite*	593 gr	€ 279,6
cranck set	Stronglight**	610 gr	n.a.
wheel set	Mavic Ksyrium elite balck	1600 gr	€ 327,0
wheel set	American Classic Sprint 350 ***	1340 gr	€ 265,0

* E-Bone QRC: 3D CNC integrated crancks (489 gr), SSP design (pat.Pending), integrated chainring spider, oversize axle and bearings
 BTC 110 mm (compact), black anodized with laser etched graphics
 Octa Ramp RC: 50-34 chainring set (95 gr), CNC AL 7075 T6 Teflon coated surface, 5 shifting ramp
 Extra Bolts 1.1: Chainring bolts set (9 gr), CNC AL 7075 T6, self locking nuts
 (complete set: crancks-axle-spider, cups & bearings, chainrings, bolts)

** Pulsion CT2 cranck set (430 gr) Full Carbon Tecnology
 53-39 chainrings, CNC AL 7075 T6 CT2 Ceramic Teflon Treatment
 Bottom Bracket Twister SL (180 gr) Carbon fiber body, Hollow titanium axle (TA6V-GR5) ISIS Drive

*** 28 spokes front 2/1.8/2 - 32 spokes rear 2/1.8/2 - rider weight limit 100 kg 220 pounds

prices in euro without ship cost VAT and duty
 prices and specifications subject to change without notice

geometry

wheel size	650c
wheel base	43" 110 cm
head tube angle	70°
seat angle	25-40°
seat height	24.5" 62 cm
medium BB height	32" 82 cm
size	X-seam (in / cm) 37-46 / 95-118

riders with X-seam lower than 37" / 95 cm have to order optional short boom

riders with X-seam higher than 46" / 118 cm have to order optional long boom

IMPROVED GEOMETRY

1. The new Slyway recumbent bikes frames have a shorter wheel base for a better control in corners.
2. Shorter rear frame, and smaller rear droppouts, in order to save weight and improve geometry.
3. Seat position is set a little back respect to the old frame. This give you a better weight distribution and great stability.
4. Morpheus seat is equipped with a new multi-pivot system.

THE BEST ERGONOMY

1. New Morpheus seat multi-pivot system (9 positions) allow you to adjust the bottom bracket - seat difference in height: this is very important to push on pedals in the best way.
2. Seat angle is also adjustable from 25° to 40° with 9 seatpost pivot point.
3. Morpheus seat feature an upper sliding section for perfect size adaptability and best comfort.
4. Slyway Fixy stem feature adjustable handlebar angle for best wrists and arms comfort.

GREAT MECHANICS

1. New Morpheus seat is 125 gr lighter than previous edition.
2. V-post CNC seatpost with an improved design, is 100 gr lighter than previous edition.
3. Bike frame is designed for a smooth and low friction chain line.
4. Rear dropout feature a replaceable rear derailleur hanger.
5. Long front derailleur tube, allow you to use oversize chain rings.
6. Aluminium alloy eccentric ring, allow you to micro-adjust the front derailleur position.